

Standard Equipment

- Dual swivel head to 60 left to 60 degrees right
- Semi- Automatic cycle
- Movable control console
- Rapid head down approach
- Carbide faced saw guide inserts
- Programmable material height sensor
- Full stroke hydraulic vise
- Driven band cleaning brushes
- Infinite band speed controlled by variable frequency drive
- Heavy duty counter balance springs
- Cast steel band wheels
- Fine adjustment head feed control
- Manual band tension
- Recirculating coolant system
- Mist band lubricator system
- Digitally displayed angle position.

Specifications:

- Capacity at 90° Rectangle: 19.5" x 13"
- Capacity at 90° Round: 14"
- Capacity at 45° Rectangle: 16.5" x 12"
- Capacity at 45° Round: 14"
- Band Width: 1 1/4"
- Band Length: 188"
- Band Speed: Variable, 65-328 fpm
- Band Tension: Manual
- Hydraulic Motor Hp: .5 HP
- Hydraulic System Reservoir Size 3 Gallon
- Coolant System Motor Hp: .6 Hp
- Coolant System Reservoir System: 5 Gallon
- Floor Space Dimensions: 114" x 43" x 56"
- Material Pass Line Height: 32"
- Machine Weight: 1,631 lbs
- Electrical Voltage Requirement: 230V or 460-6 OHZ-3ph, Wye Configuration, (Must Specify at Order Placement)
- Total Amp Draw (FLA)(460V-7)(230V-14)

DS-500SA 13" x 19.5"



Shown with 360-HP option & optional nesting



Optional Accessories:

- Heavy-duty input conveyor
- Input or output conveyor
- 5 ft Idler conveyor
- 10 ft Idler conveyor
- Additional conveyor roller
- Single fixed vertical guide
- Single adjustable vertical guide roller
- Hydraulic vertical clamp for nesting
- Laser line generator
- 5 ft. Tape work stop (Mounts on Conveyor)
- 10 ft. Tape work stop (Mounts on Conveyor)
- DoALL Cut Above 10 Year Warranty
- Custom welded to length band saw blades
- Magnetic wand chip remover
- Wear parts service kit

**In Stock
Buy Now**

